






Rhombiques tangentielles

Tiger-tec®



Plaquettes amovibles

Désignation	Classe de tolérance	Nombre d'arêtes de coupe	l ₂ mm	l mm	s mm	r mm	P			M		K			N		S		H
							HC			HC		HC			HC	HW	HC		HC
							WKP255	WKP355	WSP45	WSM35	WSP45	WAK15	WKK25	WKP255	WKP355	WXN15	WK10	WSM35	WSP45
 LNHU080304-B57T	H	4	9	8	3,5	0,4		⊗				⊗	⊗						
LNHU080404-B57T	H	4	9,4	8	4,5	0,4		⊗				⊗	⊗						
LNHU100508-B57T	H	4	12,3	10	5,5	0,8		⊗				⊗	⊗						
LNHU120608-B57T	H	4	13,9	12	6,5	0,8		⊗				⊗	⊗						
LNHU160812-B57T	H	4	16	17,4	8	1,2		⊗				⊗	⊗						
 LNHU080304-F57T	H	4	9	8	3,5	0,4	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	
LNHU080404-F57T	H	4	9,4	8	4,5	0,4	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	
LNHU100508-F57T	H	4	12,3	10	5,5	0,8	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	
LNHU120608-F57T	H	4	13,9	12	6,5	0,8	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	
LNHU160812-F57T	H	4	16	16,9	8	1,2	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	
 LNMU080304-B57T	M	4	8	9	3,5	0,4		⊗				⊗	⊗						
LNMU080404-B57T	M	4	9,4	8	4,5	0,4		⊗				⊗	⊗						
LNMU100508-B57T	M	4	12,3	10	5,5	0,8		⊗				⊗	⊗						
LNMU120608-B57T	M	4	13,9	12	6,5	0,8		⊗				⊗	⊗						
LNMU160812-B57T	M	4	16	16,9	8	1,2		⊗				⊗	⊗						
 LNMU080304-F57T	M	4	8	9	3,5	0,4	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	
LNMU080404-F57T	M	4	9,4	8	4,5	0,4	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	
LNMU100508-F57T	M	4	12,3	10	5,5	0,8	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	
LNMU120608-F57T	M	4	13,9	12	6,5	0,8	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	
LNMU160812-F57T	M	4	16	16,9	8	1,2	⊕	⊗	⊗	⊗	⊗		⊕	⊗			⊗	⊗	

HC = carbure revêtu
HW = carbure non revêtu