


## Einsatzhülsen für MK mit Lappen DIN 6383


Morse taper adaptor for flat tang

Douilles intermédiaires à cone morse



**Form AD**

zentrale Kühlmittelzufuhr  
coolant through center  
eau de refroid. centrale



**Form AD/B**

kombinierbare Kühlmittelzufuhr  
combined coolant version  
eau de refroidissement combiné

Rundlaufabweichung max 10µm  
Max runout: 10µm  
Faux-rond admissible: 10µm max.

	BT	x	MK	x	A	D	L	Artikel-Nr.
<b>BT</b> <b>30</b>	30	x	1	x	45	25	93	G460 30x1x 45
	30	x	2	x	60	32	108	G460 30x2x 60
	30	x	3	x	77	40	125	G460 30x3x 77
<b>BT</b> <b>40</b>	40	x	1	x	50	25	116	G460 40x1x 50
	40	x	2	x	50	32	116	G460 40x2x 50
	40	x	3	x	70	40	136	G460 40x3x 70
	40	x	4	x	95	48	161	G460 40x4x 95
<b>BT</b> <b>50</b>	50	x	1	x	45	25	147	G460 50x1x 45
	50	x	2	x	50	32	152	G460 50x2x 50
	50	x	3	x	65	40	167	G460 50x3x 65
	50	x	4	x	95	48	197	G460 50x4x 95
	50	x	5	x	105	63	207	G460 50x5x105