





Tool Maker Vise



- Made of SK material of J.I.S. specification.
- Hardened by heat treatment and precision ground.
- Squareness and parallelism are ensured to be within $\pm 0.005\text{mm}$.
- It can be used and kept its high precision while standing on its base, sides or extremity, for inspection use in stead of squares due to its extremely accuracy.

Unit:mm

ORDER NO.	MATERIAL	LENGTH	WIDTH	JAW OPENING	JAW HEIGHT	HEIGHT (mm)	h	HARDEN	N.W (KGS)	CODE NO
VMV-15	SK2	100	36	40	20	45	25	HRC54° $\pm 2^\circ$	0.9	2003-010
VMV-20	SK2	150	48	75	29.5	57	28	HRC54° $\pm 2^\circ$	2	2003-011
VMV-25	SK2	170	63	90	35	62	28	HRC54° $\pm 2^\circ$	3.3	2003-012
VMV-30	SK2	190	73	100	35	67	32	HRC54° $\pm 2^\circ$	4.5	2003-013
VMV-35	SK2	225	88	125	45	84.5	40	HRC54° $\pm 2^\circ$	7	2003-014
VMV-40	SK2	230	98	125	45	85	40	HRC54° $\pm 2^\circ$	8.9	2003-015
VMV-50	SK2	287	125	150	50	100	50	HRC54° $\pm 2^\circ$	15.5	2003-016
VMV-60	S50C	330	150	200	50	100.5	50	HRC54° $\pm 2^\circ$	21.4	2003-017