



适用范围: 有色金属及塑料, 非金属等
切削加工。

特征:

1. 高精度短圆柱连接。
2. 易损部件都经过特殊淬火处理, 有效地提高耐磨性和使用寿命。
3. 单动调整中心, 可用于各种形状加工, 更大的夹紧力。

Application: Recommended for processing of non-ferrous metals, non-metals like plastics and so on.

Features:

1. High precision short cylindrical center mounting.
2. Flimsy parts are specifically engineered by quenching, for greater durability and extended life.
3. Adjusted independently to center, suitable for processing special with superior gripping force.



规格Size mm	D1	D2	D3	H1	h	z-d	净重kg Net WT	极限转速r/min Max.speed
80	55	66	22	42	4	4-M6	2.5	4800
100	72	84	25	54	4	4-M8	3	4800
125	95	108	30	56	4.5	4-M8	5	4200
160	65	95	55	65	5	4-M10	9	3800
200	80	112	70	71	6	4-M10	15	2100
250	110	130	100	80	6	4-M12	23	1800
300	152	130	95	100	6	4-M12	39	1400
320	140	165	115	100	6	4-M16	40	1400
350	130	168	115	100	6	4-M16	53	1400
400	160	185	125	100	8	4-M16	55	950
500	200	236	170	106	8	4-M20	102	600
630	220	258	180	118	10	4-M20	159	500
800	250	300	220	135	12	8-M20	/	500
1000	320	370	305	152.5	15	8-M20	/	400
1250	400	500	380	165	15	8-M20	/	300